

## E3 ENTRY 4.3" SPECIFICATIONS

|   |   |
|---|---|
| ITEM  | e3 Entry 4.3" - Order Number EN-2A4 (ArmorTech) EN-2M4 (Metal)                          |
| Warranty  | 2 Years Hardware and Software - Optional 4 Year Add on warranty for total of 5 years    |
| UL294 Series 6  | UL294 Series 6, Attack class 2, ROHS, FCC   |
| Available Modules   | 2-Door Module, 4 Door Modules   |
| System Integrity  | 128 bit Encryption (User database and events) / SSL / HTTPS / PHP                       |
| Language  | English   |
| System Control  | Fully browser controllable  |
| Pre Configured Doors Per System                               | 2 on board, expandable I/O (2/2) up to 36 doors   |
| Max Readers per system  | Expandable up to 72 in/out  |
| Max Modules - Sites per system                                | 32  |
| Distributed Processing  | Every module contains database and events (Each unit process transactions)              |
| Outputs Per Board   | 4 Form C SPDT / Dry 5 Amp   |
| Outputs Times   | Hours, Min, Sec., by set time and or repeat quantity.                                   |
| e-Mail and SMS Notification                                   | Yes   |
| Inputs per board  | 8- 6 Analog Selectable for type, 2 Pre-assigned (Tamper, Postal)                        |
| Input types   | NO / NC Parallel Resistor, NO / NC Series Resistor, NO / NC Unsupervised                |
| Predefined Door Configuration                                 | Lock, Prop (Output) REX, Door Position (Input)  |
| Expansion Modules   | 8   |
| Environmental Temperature                                     | -22°F to 149°F (-30°C to 65°C) Humidity: 5% to 95% non-condensing                       |
| <b>EVENT ACTION</b>   |   |
| Event Action Input  | Reader Event, Physical Input, Door Position, REX, System Event, API                     |
| Event Action Output   | Outputs, Dashboard, eMail, SMS, Back up SD / FTP, Threat level, Video tag               |
| Power (per board)   | 12VDC from provided DC plug in power supply - Power for two modules & readers           |
| Battery Charging  | 2 / 7AH Batteries   |
| Total System Access Levels                                    | 250   |
| Users per system  | 10 000  |
| User Photos   | 10 000  |
| Access cards  | 120,000   |
| Cards per person  | 32  |
| Binary Card Decoder   | Yes - 26 - 128 bit with or with out facility code, Facility Code Only                   |
| User-defined data fields                                      | 20 user fields, Flat File Import Option   |
| Integrated Flat File Database Import Tool                     | Yes, CSV and TXT  |
| Day Light Savings Time "DST"                                  | Automatic , Editable dates if future requirement  |
| SMTP  | On / Off Manual, PC Sync  |
| Client Time Zone Configuration                                | Yes, Each module is selectable  |
| Time specifications (schedules)                               | 250   |
| Time spec groups (Schedule groups)                            | 64  |
| Holidays, Holiday Groups                                      | 60, 4 groups  |
| Online event history log                                      | 50,000 transactions   |
| Transaction Types   | Action of any type, Administrator Change Logging "Audit", and System Diagnostic Events. |
| Archive for transactions                                      | Manual, Automatic daily, Automatic by 90% full - Up to 500K per archive offline FTP     |
| Archive for system configuration files                        | Manual, Automatic daily   |
| FTP Off Controller Report Utility (Seamless thru existing UI) | Yes, 500K+ transaction files  |
| Administration / User Roles                                   | Super for Entire System, Admin designated by doors (building), Customizable by Users    |
| Maximum concurrent web users                                  | 25  |
| Maximum defined administrative users                          | 160   |
| Remote Management Console                                     | Optional  |
| <b>USER INTERFACE FEATURES</b>                                |   |
| System Fully Web Controllable                                 | Yes   |
| Action Icons  | Door Unlock, Toggle, Aux outputs  |
| Alarm Acknowledgement   | Yes   |
| Logo Placement  | Yes - Ability to place Dealer or End user logo into system                              |