




# HSLG

## Model

### HSLG COMMERCIAL/ INDUSTRIAL

- Integral APeX Controller
- Double V-belt to chain reduction
- #40 roller drive chain
- 1/2, 3/4, or 1 HP motor
- All voltages, single or three-phase
- Powder coat finish
- Post mount standard; pad mount optional



### HSLG SERIES SLIDE GATE OPERATOR SPECIFICATIONS

	Model	HP	Voltage Single-Phase (Voltage Three-Phase)	Maximum Gate Length	Maximum Gate Weight	Gate Speed	Shipping Weight
HSLG	HSLG-2	1/2	115 / 230 VAC (208 / 230 / 460 VAC)	35'	1000 lbs	10" / second	280 lbs
	HSLG-4	3/4	115 / 230 VAC (208 / 230 / 460 VAC)	45'	1200 lbs	10" / second	285 lbs
	HSLG-1	1	115 / 230 VAC (208 / 230 / 460 VAC)	55'	1700 lbs	10" / second	290 lbs

# HSLG Features

## Electrical

- Solid state 24V control board UL325/UL991 compliant
- Diagnostic LED display for ease of setup and trouble shooting
- Integral entrapment sensing system with digital set point for accurate adjustment and enhanced safety
- Integrated maximum run and auto close timers
- Built-in dual gate capability using 3-wire shielded cable
- 24V DC power available for access control accessories
- Continuous-tone entrapment alarm with reset button
- Integrated warning beeper during gate movement

- Selectable pre-start alarm with provision for ADA compliant visual pre-start and run alarm
- Solenoid disc brake

## Mechanical

- Heavy duty steel chassis
- Easy-to-operate emergency manual disconnect handle
- #40 roller chain and sprockets
- Efficient double V-belt drive
- Heavy duty pillow-block bearings
- Adjustable torque limiter

### 1 APeX Controls

- UL325/UL991 compliant 24VDC control module
- Full featured for access control, security, and entrapment protection
- Integral MegaCode receiver
- On-board 3-button station

### 2 Belt and Chain Reduction

- Rugged and efficient double, 4L V-belt to chain reduction

### 3 Manual Disconnect

- Secure, easy, manual operation during power failure or emergency
- Optional remote cable kit for outside-the-gate access

### 4 Heavy Duty Components

- Adjustable torque limiter and heavy-duty pillow block bearings for smooth, reliable, quiet power transmission
- All models rated for continuous duty

### 5 Weather-Resistant Cabinet

- Galvannealed steel cabinet with powder coat finish
- Lockable, gasketed, hinged, and removable front cover

### 6 Standard Convenience Features

- Exterior stop/reset button
- Power on/off button



**CAUTION**

- Automatic gates not for pedestrians
- Automatic gate operators designed for vehicular traffic only; operators are powerful and can cause serious injury or death; DIRECT ALL PEDESTRIAN TRAFFIC TO SEPARATE PEDESTRIAN GATE
- UL325 requires use of contact or non-contact anti-entrapment devices
- ASTM F2200 requires that all exposed rollers are covered

**LINEAR**  
a Nice brand

## Linear® Garage Door Operators, Gate Operators, Access Controls and Radio Controls

*Backed by 60 years of pioneering experience in wireless technology, garage door and gate operator manufacturing, and access control systems, the full breadth of the Linear® brand is a leading source for the garage door, gate, and access industries.*

**Nice**

223143 Rev-F 02/2023

[www.LinearGateOpeners.com](http://www.LinearGateOpeners.com) | (888) 378-1053 | [Sales@LinearGateOpeners.com](mailto:Sales@LinearGateOpeners.com)